




Comparison of SonoPro® Portable Ultrasonic Flowmeters

		SonoPro® Portable (Model U44)	SonoPro® Professional Series Portable (Model S34)
			
FEATURES/SPECIFICATIONS	Pipe Sizes	1" to 48" (25 mm to 1200 mm)	1/2" to 200" (15 mm to 5000 mm)
	Acceptable Fluids	Most clean liquids (Minimal air bubbles and/or particles)	Most clean liquids (Minimal air bubbles and/or particles)
	Accuracy	±1% of reading	>1-inch pipe size: ±1% of reading ≤1-inch pipe size: ±2% of reading
	Velocity Range	0.03 ft/s to 40 ft/s (0.01 m/s to 12 m/s)	0.03 ft/s to 40 ft/s (0.01 m/s to 12 m/s)
	Datalogging	Yes	Yes
	Advanced Datalogging Tools	None	SonoConfig™ Instrument Interface Software (Android® App)
	Advanced Diagnostic Tools	None	SonoConfig™ Instrument Interface Software (Android® App)
	Mass Flow Metering	No	Yes
	Energy (BTU) Metering	Optional	Optional
	Bluetooth® Communications	None	Optional

Phone: (303) 682-9999 • Email: info@vortekinst.com • www.vortekinst.com